

TECHNICAL DATA

Fluke TPS Shunt 20MA



Specifications: Fluke TPS Shunt 20MA

General Specifications	
Measuring Range selectable per software	0 to 55 mA
Peak current for sinusoidal currents	77.8 mA $I_{max} = 1.5 \text{ A}$
Intrinsic error	0.2%
Frequency Range	DC to 3.0 kHz
Operating Voltage	300 V CAT IV
Phase Error	0.1°
Jaw Opening	-
Errors in % of measuring range at $23^{\circ}\text{C} \pm 2 \text{ K}$; $74^{\circ}\text{F} \pm 2 \text{ K}$, for 48 to 65 Hz Phase angle error at nominal current I_{max} maximum current without time limit (for AC and DC shunts)	

Ordering information



TPS SHUNT 20MA

Part#: 2540553

UPC#: 095969325806

Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2026 Fluke Corporation.
Specifications subject to change without notice.
08/2026

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**