

TECHNICAL DATA

AC288 Terminal Block Probe with Retractable Probe Tip



Key features

- Retractable probe tip designed for increased safety, while providing flexibility to reach deep connection points
- Recommended for use with TL224, TL222 or TL221 Test Leads
- 11.5 cm (4.5 in) insulated, flexible shaft
- 1 mm diameter probe tip extends out to 8.4 mm (0.33 in) length
- Retractable probe tip is made with stainless steel
- Safety rated: IEC 61010-031, CAT III 1000 V, CAT IV 600 V
- Operating temperature: -20 °C to 55 °C (-4 °F to 131 °F), 90% RH
- One-year warranty

Product overview: AC288 Terminal Block Probe with Retractable Probe Tip

Use for safe and secure connections to clamp and screw type terminal blocks.

Ordering information

**AC288**

Part#: 4617784

UPC#: 095969783538



Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2026 Fluke Corporation.
Specifications subject to change without notice.
08/2026

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**